



FLOOD LIGHT 100W Model : OPTO FD 02

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
DRIVER	: CE
POWER	: 100W \pm 10%
LUMINOUS FLUX	: 10,000lm
EFFICACY	: 100lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: >100°
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C To -50°C
LIGHTING SOURCE LIFE	: 50,000Hrs.
IP PROTECTION RATING	: IP66

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS





FLOOD LIGHT 100W Model : OPTO FD 02

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305VAC
LED CHIP	: SMD
DRIVER	: CE
POWER	: 150W±10%
LUMINOUS FLUX	: 15,000lm
EFFICACY	: 100lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: >100°
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C TO -50°C
LIGHTING SOURCE LIFE	: 50,000Hrs.
IP PROTECTION RATING	: IP66



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS